



## TES-1372R CO METER

### Product Features

- CO : 0 ~ 999 ppm range.
- MAX Hold with Time stamp.
- Alarm level setting.
- Replaceable sensor extends meter life.
- Stabilized electrochemical CO sensor.
- Automatic sensor zeroing upon start-up.
- Auto power-off time setting.
- Typical three year sensor life, one year calibration cycle.
- Manual data memory and read function (99 sets).
- Auto data memory and read function (999 sets).
- Auto Datalogger (11340 sets) and RS232 PC interface.
- Backlight display function.

Measuring Range	0~ 999 ppm
<b>Resolution</b>	1ppm
<b>Accuracy</b>	±5% of reading or ±5ppm, which is greater.
<b>Sensor Type</b>	Stabilized electrochemical Gas-specific (CO)
<b>Typical Sensor Life</b>	3 years
<b>Auto Data Memory Capacity</b>	999 sets (Direct reading from LCD display)
<b>Manual Data Memory Capacity</b>	99 sets (Direct reading from LCD display)
<b>Auto Datalogger Capacity</b>	11340 sets (Only download by PC).
<b>Operating Conditions</b>	0°C~ +50°C 15 ~ 90% R.H.
<b>Power Source</b>	9V battery
<b>Battery Life</b>	Approx. 100 hours
<b>Size</b>	173(L) × 50(W) × 50(H)mm
<b>Weight</b>	Approx. 180g with battery.
<b>Accessories</b>	Instruction Manual, Battery & Carrying case. Instruction Manual, Battery, CD Software, RS232 Cable & Carrying case.