

TES

Reliable in Quality

TES-1260 Humidity Temperature Meter

- ❑ Slimline and Stylish
- ❑ Large Dual LCD display.
- ❑ Dew Point Reading / Wet bulb Reading.
- ❑ MAX/MIN with Time Stamp.
- ❑ Data Hold function.
- ❑ °C / °F Switchable.
- ❑ DATA memory and read function.

(99 readings from LCD display)




Wall Mount



Dew Point Reading



Wet bulb Reading



MAX/MIN with Time Stamp





Reliable in Quality

1260 Humidity Temperature Meter

FEATURES

- Dual LCD display.
- Dew Point Reading.
- Wet bulb Reading.
- MAX/MIN with Time Stamp.
- Data Hold function.
- °C / °F Switchable.
- DATA memory and read function.
(99 readings from LCD display)
- Auto Power Off.

SPECIFICATIONS

Measuring Range	Temperature : -20°C ~ 60°C (-4°F ~ 140°F) Humidity : 1%RH ~ 99%RH
Resolution	0.1°C / 0.1°F / 0.1%RH
Accuracy	Temperature : ±0.5°C, ±0.9°F Humidity : ±3%RH (at 25°C, 30 ~ 99% RH). ±5%RH (at 25°C, 1 ~ 30% RH).
Data Memory capacity	Manual recording : 99 data sets. (Direct reading from LCD display.)
Sampling Rate	2 times/sec
Operating Conditions	0°C ~ 60°C (32°F ~ 140°F) & below 99% R.H. (no condensation)
Power Source	9V Battery
Battery Life	Approx. 300 hours.
Size & Weight	193mm(L) × 59mm(W) × 26mm(H) / 140g
Accessories	Instruction manual, Battery.



TES ELECTRICAL ELECTRONIC CORP.

7F, No.31 Lane 513, Rui Guang Rd., Neihu Dist, Taipei, Taiwan

Tel : (02) 2799-3660 Fax : 886-2-2799-5099

E-mail : tes@ms9.hinet.net

<http://www.tes.com.tw>